



XL2000 wide



max width

2000 mm

main rolls \varnothing

150 mm

max. temperature

120 °C

max. material thickness

50 mm

New friction poles ☐



Ventilation to avoid bubbles β



Trimming Blades Kit Included ☐



>XL2000 wide

PNEUMATIC HOT LAMINATOR (120°C)



Unique features!

Hot roll-to-roll pneumatic laminator 2000 mm. Complete with rewinder. **Silicone roller (heated) 150mm**, maximum temperature **120°C**. **Material thickness up to 50mm**. Ventilation to avoid bubbles.

Quick and easy to use, it allows you to save labor and improve productivity by increasing the quality of your work. Also, from today you can laminate also without liner with **"linerless" laminations**.

High efficiency

No creases or bubbles, it guarantees excellent results even at temperatures below 120°C. **Equipped with pedal feed**, it allows the operator to keep both hands free for the lamination of larger media.

Safety warranty

The **photocell sensor** prevents you from bringing your hands together during lamination. The emergency stop buttons are clearly visible on the upper side of the machine.

Product code
XL2000WIDE

Main silicone roller diameter
150 mm

Packaging
anti-shock wooden

Max lamination film width
2000 mm

Roll handling
by air compresso

Dimensions (l x h x p)
2300 x 1500 x 900 mm

Maximum material thickness
50 mm

Footswitch feeding
included

Packaging dimensions (l x h x p)
2500 x 1680 x 1000 mm

Maximum temperature
120 °C

Take-Up system
included

Machine weight / packaging weight
445kg / 620kg

Minimum - maximum speed
2,30 - 30,00 lmt/min

Heating method
Internal with infrared light

Safety
photocell / CE certification

Temperature / speed control
Micro Control

Power / Voltage
0,8-1,0 kw/h - 220 v - 50 hz

Warranty
12 months



Authorized Reseller

DicanDigital®

Nuestro mayor patrimonio son nuestros clientes satisfechos