



www.xlam.biz

Xlam

XL1600 cold&hot 3.0



main rolls Ø

130 mm

max. temperature

120 °C

max. material thickness

30 mm

Micrometric speed controller ✓



End of material sensor ↑



New Front and Back Displays 👍



XL1600 cold&hot 3.0



PNEUMATIC HOT LAMINATOR UP TO 120°C

www.xlam.biz / info@xlam.biz

Unique features!

Pneumatic roll-to-roll hot laminator 1600 mm. Complete with rewinder. **Silicone roller (heated)** diameter 130mm, maximum temperature 120°C. Material thickness up to 30mm.

Quick and easy to use, it allows you to save labor and improve productivity by increasing the quality of your work. Also, from today you can laminate also without liner with **"linerless" laminations**.

High efficiency

No creases or bubbles, it guarantees excellent results even at temperatures below 120°C. Equipped with **pedal feed**, it allows the operator to keep both hands free for the lamination of larger media.

Safety warranty

The **photocell sensor** prevents you place your hands near roll during the lamination. The emergency shutdown button is clearly visible on the front of the machine.

Model

Xlam 1600 Cold&Hot 3.0

Silicone rollers diameter

130 mm

Maximum power / Voltage

2500 W / 220 v (three-phase) - 50 hz

Product code

XL1600CH3.0

Roll lifting

by air compressor

Dimensions (l x h x d)

2050 x 1300 x 700 mm

Maximum lamination width

1600 mm

Pedal feeding

included

Packaging Dimensions (l x h x d)

2250 X 740 x 840 mm

Maximum material thickness

30 mm

Warm-up time

10-15 minutes

Machine weight / Packaging weight

175 kg / 195 kg

Maximum temperature

120 °C

Heating method

internal with incandescent lamp

Safety

photocell / CE certification

Minimum - maximum speed

2,30 - 12,80 lmt/min

Temperature / speed control

Micro Control

Warranty

12 months

FUNCTIONAL NEWS:

End of material sensor

Reinforced structure of the stand and of the machine body

Integrative back panel

NEW FRONT AND BACK DISPLAYS:

Lmt/min counter

METER key (possibility of resetting measured meters)

LIFT button (roller lifting directly from the display)

Auto/pause key (disables the material end sensor)

NEW ELECTRICAL COMPONENTS:

Inverter to regulate the motor functions

220v three-phase roller drive motor

Authorized Reseller