

Product Data Sheet

Avery Dennison® Frosted Glass Window Film

Issued: 03/2021

Introduction

Avery Dennison Frosted Glass Window Film is suitable for decorative and functional graphics on glass windows and screens, doors and mirrors. Avery Dennison Frosted Glass Window Film is especially developed for computer-aided signmaking systems and has a frosted glass appearance. Avery Dennison Frosted Glass Window Film is a quality cast film offering an indoor durability of up to 15 years.

Conversion

Avery Dennison Frosted Glass Film has been especially developed for conversion on a wide range of computerised signmaking equipment.

Printability

Avery Dennison frosted Glass Window Film is a good candidate for screen and digital printing. However a print test prior to application is strongly recommended.



Face Film

80 micron cast film with frosted glass appearance



Adhesive

permanent, acrylic based




Backing paper

one side coated bleached kraft paper, 135 g/m²



Durability

Up to 7 years outdoors (vertical exposure)



Shelf life

2 years
stored at 22°C/ 50% RH

Recommendations for use

The Avery Dennison Frosted Glass Window Film is specially developed to create the image of frosted decorations on glass, as well as functional and manifestation graphics. Avery Dennison Frosted Glass Window Film can be applied on flat surfaces, and is best used on transparent surfaces like glass, acrylic sheets and polycarbonate materials.

- Flat surfaces only
- High tack application tape
- Application to a substrate with the wet method will facilitate positioning
- Addition of 0,5 % of neutral detergent to water will give you the right application fluid
- Water to be removed with a squeegee and firm hand pressure
- Allow the adhesive to build up sufficient adhesion level (this may take 15-45 minutes!) before application tape removal
- Due to its unique finish, variances in appearance can be visible when the material is oriented in different directions. When utilizing Frosted Glass Window Film, always keep the application direction of the film consistent with the orientation of the film when cut from the roll and applied to the glass.

Features

- Durability: 15 years (indoor) / 7 years (outdoor)
- Brilliant visual frosted effect
- Excellent dimensional stability and layflatness during use and application
- New liner imprint design with square pattern to support manual conversion
- Easy cutting and weeding
- Excellent conversion properties on computerised signmaking
- Excellent adhesion
- Product width: 1.23m

Physical Characteristics

Features	Test method ¹	Results
Caliper, facefilm	ISO 534	80 micron
Caliper, facefilm + adhesive	ISO 534	115 micron
Gloss	ISO 2813, 20°	15%
Dimensional stability	DIN 30646	0,20 mm. max
Tensile strength	DIN 53445	1 kN/m
Elongation at break	DIN 53445	25%
Adhesion, initial	FINAT FTM-1, stainless steel	400 N/m
Adhesion, ultimate	FINAT FTM-1, stainless steel Glass PMMA/Polycarbonate	480 N/m 500 N/m 640 N/m
Flammability		Self-extinguishing
Shelf life	Stored at 22°C/50%RH	2 years
Durability ²	Vertical exposure	Indoor: 15 years Outdoor: 7 years
Temperature range		
Application temperature		Minimum +10°C
Temperature range		-40°C to +90°C
Chemical resistance		
Humidity resistance	200 hours exposure	No effect
Water resistance	24 hours immersion	No effect
Detergent (1% solution)	24 hours immersion	No effect
Detergent solution 65°C	8 hours immersion	No effect
Isopropyl Alcohol / Water (20/80)	10 minutes immersion	No effect

1) Test methods: More information about our test methods can be found on our website.

2) Durability: durability is based on middle European exposure conditions. Actual performance life will depend on substrate preparation, exposure conditions and maintenance of the marking. For instance, in the case of signs facing south; in areas of long high temperature exposure such as southern European countries; in industrially polluted areas or high altitudes, exterior performance will be decreased.

Important notice Information on physical and chemical characteristics and values in this document are based upon tests we believe to be reliable and do not constitute a warranty. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material to their specific use.

All technical data are subject to change. In case of any ambiguities or differences between the English and foreign versions of this document, the English version shall be prevailing and leading.

Disclaimer and warranty Avery Dennison warrants that its Products meet its specifications. Avery Dennison gives no other express or implied guarantees or warranties with respect to the Products, including, but not limited to, any implied warranties of merchantability, fitness for any particular use and/or non infringement. All Avery Dennison products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purposes. The period of warranty is one (1) year from the date of shipment unless expressly provided otherwise in the product data sheet. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see <http://terms.europe.averydennison.com>. Avery Dennison's aggregate liability to Purchaser, whether for negligence, breach of contract, misrepresentation or otherwise, shall in no circumstances exceed the price of the defective, non-conforming, damaged or undelivered Products which give rise to such liability as determined by net price invoices to Purchaser in respect of any occurrence or series of occurrences. In no circumstances shall Avery Dennison be liable to Purchaser for any indirect, incidental or consequential loss, damage or injury, including without limitation, loss of anticipated profits, goodwill, reputation, or losses or expenses resulting from third party claims.